



# GOLD SERIES

## Commerical Grade Power Protection

**PRO-EDGE** 10 to 300 kVA (kW) THREE PHASE POWER REGULATOR

### NOTES

- Terminal Blocks Accessed Through Top
- Front Service Clearance Only
- No Side or Rear Access Required
- Internal Shunt Trip Input Breaker
- 50 Foot REPO Cable has One Connector Removed for 1/2 Inch Conduit Routing and Site Attachment
- Operating Temperature 0° C to 40° C
- Castors
- Parity Sized Ground Conductors are Recommended
- OCPD = Over Current Protection Device
- All Wiring Per Local/ National Electrical Codes
- Output OCPD (optional)

### Site Planning Guide

Model Selector	Power Rating		Voltage		Standard AC Input		AC Output		Mechanical Data		
	kVA	kW	Input	Output	Current (A)	Rec. OCPD	Current		Dimensions WxDxH, in.	Weight lb.	Heat Dis. BTU/h
					Nom.		Nom.	OCPD			
WDC 3010 R	10	10	208	208	29	35	28	35	29x30x72	450	1,050
	10	10	480	208	12	15	28	35	29x30x72	450	1,050
	10	10	480	480	12	15	12	15	29x30x72	450	1,050
WDC 3015 R	15	15	208	208	43	50	42	60	29x30x72	475	1,580
	15	15	480	208	19	25	42	60	29x30x72	475	1,580
	15	15	480	480	19	25	18	25	29x30x72	475	1,580
WDC 3020 R	20	20	208	208	57	70	56	80	29x30x72	550	2,100
	20	20	480	208	25	30	56	80	29x30x72	550	2,100
	20	20	480	480	25	30	24	30	29x30x72	550	2,100
WDC 3030 R	30	30	208	208	86	100	83	125	29x30x72	990	3,160
	30	30	480	208	37	45	83	125	29x30x72	990	3,160
	30	30	480	480	37	45	36	50	29x30x72	990	3,160
WDC 3050 R	50	50	208	208	143	175	139	175	29x30x72	1,250	5,260
	50	50	480	208	62	75	139	175	29x30x72	1,250	5,260
	50	50	480	480	62	75	60	80	29x30x72	1,250	5,260
WDC 3075 R	75	75	208	208	215	250	208	300	29x30x72	1,650	7,900
	75	75	480	208	93	125	208	300	29x30x72	1,650	7,900
	75	75	480	480	93	125	90	125	29x30x72	1,650	7,900
WDC 3100 R	100	100	208	208	286	350	278	350	29x30x72	1,800	10,530
	100	100	480	208	124	150	278	350	29x30x72	1,800	10,530
	100	100	480	480	124	150	120	150	29x30x72	1,800	10,530
WDC 3125 R	125	125	480	208	155	200	347	450	37x30x72	1,900	13,170
	125	125	480	480	155	200	151	200	37x30x72	1,900	13,170
WDC 3150 R	150	150	480	208	186	250	417	550	37x30x72	2,000	16,850
	150	150	480	480	186	250	181	225	37x30x72	2,000	16,850
WDC 3200 R	200	200	480	208	248	300	556	600	37x30x72	2,240	16,850
	200	200	480	480	248	300	241	250	37x30x72	2,240	16,850
WDC 3250 R	250	250	480	208	310	400	695	900	60x30x72	2,390	25,280
	250	250	480	480	310	400	301	375	60x30x72	2,390	25,280
WDC 3300 R	300	300	480	480	372	450	361	400	60x30x72	2,590	31,640

**World Design Concepts & Technologies, Inc.**  
 12520 High Bluff Drive, Suite 150, San Diego, CA 92130  
 (ph) 866-649-WDC (9328) ■ (f) 858-847-9144