



# GOLD SERIES

## Commerical Grade Power Protection

**PRO-EDGE 10 TO 300 kVA THREE PHASE UPS**

### NOTES

- Terminal Blocks Accessed Through Top
- Front Service Clearance Only
- No Side or Rear Access Required
- Control Cabinet Contains an Internal Shunt Trip Input Breaker
- Battery Cabinet Contains an Internal Shunt Trip Breaker
- 50 Foot REPO Cable has One Connector Removed for 1/2 Inch Conduit Routing and Site Attachment
- Operating Temperature 0° C to 40° C
- Castors and Fork Lift Base
- Parity Sized Ground Conductors are Recommended
- OCPD = Over Current Protection Device
- All Wiring Per Local/ National Electrical Codes
- Output OCPD (optional)

## Site Planning Guide

Model Selector	Power Rating		Voltage		Standard AC Input			AC Output		Mechanical Data		
					Current (A)		Rec. OCPD	Current		Dimensions WxDxH, in. with Batteries	Weight lb.	Heat Dis. BTU/h
	Nom.	Max.	Nom.	OCPD								
WDC 3010 C	10	10	208	208	29	36	50	28	35	29x30x72	450	1,050
	10	10	480	208	12	16	25	28	35	29x30x72	450	1,050
	10	10	480	480	12	16	25	12	15	29x30x72	450	1,050
WDC 3015 C	15	15	208	208	43	54	75	42	60	29x30x72	450	1,580
	15	15	480	208	19	23	50	42	60	29x30x72	450	1,580
	15	15	480	480	19	23	50	18	25	29x30x72	450	1,580
WDC 3020 C	20	20	208	208	57	72	100	56	80	29x30x72	550	2,100
	20	20	480	208	25	31	50	56	80	29x30x72	550	2,100
	20	20	480	480	25	31	50	24	30	29x30x72	550	2,100
WDC 3030 C	30	30	208	208	86	107	150	83	125	29x30x72	2,100	3,160
	30	30	480	208	37	47	75	83	125	29x30x72	1,850	3,160
	30	30	480	480	37	47	75	36	50	29x30x72	1,850	3,160
WDC 3050 C	50	50	208	208	143	179	225	139	175	60x30x72	2,200	5,260
	50	50	480	208	62	78	100	139	175	60x30x72	1,900	5,260
	50	50	480	480	62	78	100	60	80	60x30x72	1,900	5,260
WDC 3075 C	75	75	208	208	215	269	350	208	300	60x30x72	2,500	7,900
	75	75	480	208	93	116	150	208	300	60x30x72	2,150	7,900
	75	75	480	480	93	116	150	90	125	60x30x72	2,150	7,900
WDC 3100 C	100	100	208	208	286	358	450	278	350	60x30x72	4,500	10,530
	100	100	480	208	124	155	175	278	350	60x30x72	4,500	10,530
	100	100	480	480	124	155	175	120	150	60x30x72	4,500	10,530
WDC 3125 C	125	125	480	208	155	194	250	347	450	60x30x72	4,700	13,170
	125	125	480	480	155	194	250	151	200	60x30x72	4,700	13,170
WDC 3150 C	150	150	480	208	186	233	300	417	550	60x30x72	4,900	16,850
	150	150	480	480	186	233	300	181	225	60x30x72	4,900	16,850
WDC 3200 C	200	200	480	208	248	310	350	556	600	(2) 60x30x72	5,500	16,850
	200	200	480	480	248	310	350	241	250	(2) 60x30x72	5,500	16,850
WDC 3250 C	250	250	480	208	310	388	500	695	900	(2) 60x30x72	5,600	25,280
	250	250	480	480	310	388	500	301	375	(2) 60x30x72	5,600	25,280
WDC 3300 C	300	300	480	480	372	466	600	361	400	(2) 60x30x72	5,800	31,640

**World Design Concepts & Technologies, Inc.**  
 12520 High Bluff Drive, Suite 150, San Diego, CA 92130  
 (ph) 866-649-WDCT (9328) ■ (f) 858-847-9144